

Multimeter Comparison Chart

Model	Voltage DC/AC	Current DC/AC	Resistance	Capacitance	Frequency	Temperature	Logic test	hFE	Inductance	Diode	Continuity	Features
M-3800	0.2-1000V 0.2-700V	20μA-20A 20μA-20A	200Ω-20MΩ									3 ½digit
ME-31	0.4-1000V 0.2-750V	4mA-20A 4mA-20A	400Ω-40MΩ									3 ¾digit, RS232, Bargraph, Data Hold, Software
ME-32	0.4-1000V 0.2-750V	4mA-20A 4mA-20A	400Ω-40MΩ	4nF-400nF		0°C-1000°C						3 ¾digit, RS232, Bargraph, Range-hold, Software
ME-6000	0.6-1000V 0.6-750V	600μA-20A 600μA-20A	600Ω-60MΩ	6nF-6mF	6KHz-60MHz							4 digit, Min/Max/Data hold
M-3650D	0.2-1000V 0.2-750V	200μA-20A 200μA-20A	200Ω-20MΩ 2000MΩ	2nF-200μF	2KHz-20MHz							3 ½digit, RS232, Bargraph, Dual, Logika, Software
M-3660D	0.2-1000V 0.2-750V	2mA-20A 2mA-20A	200Ω-20MΩ	2nF-200μF	2KHz-20MHz	-40°C-1200°C						3 ½digit, RS232, Bargraph, Dual, Logic test, Software
M-3870D	0.4-1000V 0.4-750V	40mA-20A 40mA-20A	400Ω-40MΩ	4nF-400μF	4KHz-4MHz	-40°C-1200°C			40mH-40H			3 ¾digit, RS232, Signal, Bargraph, Auto, Dual, Software
M-3860M	0.4-1000V 0.4-750V	400μA-20A 400μA-20A	400Ω-40MΩ	4nF-400μF	4KHz-40MHz	-40°C-1200°C						3 ¾digit, RS232, True RMS, Auto, KW , Software
M-4640A	0.2-1000V 0.2-750V	2mA-20A 2mA-20A	200Ω-20MΩ	20nF-200μF	20KHz-2MHz							4 ½digit, RS232, Memo, Logic test, Bargraph, Software
M-4660A	0.2-1000V 0,2-750V	2mA-20A 2mA-20A	200Ω-20MΩ	2nF-200μF	2KHz-20MHz	-40°C-1200°C						4 ½digit, Dual, Bargraph, Logic test, RS232, Software
M-4660M	0.2-1000V 0,2-750V	2mA-20A 2mA-20A	200Ω-20MΩ	20nF-200μF	20KHz-2MHz				200mH			4 ½digit, Dual, Bargraph, Logic test, RS232, Min/Max, AVG, Mem, KW , Cosó, Software
MXD-4660A	0.2-1000V 0.2-750V	2mA-20A 2mA-20A	200Ω- 2MΩ-20MΩ		20KHz-20MHz							4 ½digit, Tápfeszültség, RS232, True RMS, Memory, Hi-Precision, Software
P 10	0.4-400V 4-400V	2mA, 200mA 2mA, 200mA	40MΩ-ig 6 lépésben	40nF-40μF	10Hz-10MHz							3 ¾digit, Bargraph, Data Hold, beépített mérőszinór