

# Fluke 985 Particle Counter

## Technical Data

### Troubleshooting indoor air quality made easy


The particle counter is an essential tool in the facility maintenance, HVAC and IAQ professional's toolbox. From filter testing to indoor air quality investigations, the particle counter equips the user with valuable data concerning the concentration and source of particulates in the tested environment.

The new Fluke 985 Particle Counter is ideal for troubleshooting and monitoring indoor air quality issues and verifying HVAC filter performance and critical locations for ISO Class 5–9 certification.

With the ultra-light weight ergonomic design, easy to view color screen with intuitive icons, on-screen trend graphs for easy and quick analysis, the Fluke 985 is a must for any maintenance, HVAC and IAQ professional.

### Fluke 985 Particle Counter features:

- Six channels and a particle size range of 0.3  $\mu\text{m}$  to 10  $\mu\text{m}$
- Ultra-lightweight and ergonomic design for easy single-hand operation
- Ten hours of standard-use battery life to last a full work day
- Large 3.5 inch QVGC color display with backlight, intuitive icons, and large font options make for easy navigation and viewing
- 10,000 records stored in device for easy access to historical data
- Data can be viewed in traditional tabular or trend graph at the user's preference
- Configurable display, sample methods, and alarm setting for sample size count (raw count, per cubic feet, cubic meter, or liter)
- Data export to USB memory stick or direct connection to PC via USB cable. No special software required to view Excel compatible files
- Ethernet enabled for accessing data via internet browser (Windows Explorer, Safari, and Firefox)
- USB/Ethernet charge cradle ensures the unit always ready for use
- Administrator password control (optional) for added security
- Meets ISO 21501, JIS B9921, and CE standards



Profile of 0.3 to 10  $\mu\text{m}$  particles captured over 15 minutes window.

## Specifications

<b>Six size channels</b>	0.3 µm, 0.5 µm, 1.0 µm, 2.0 µm, 5.0 µm, 10.0 µm
<b>Flow rate</b>	0.1 cfm (2.83 L/min)
<b>Light source</b>	775 nm to 795 nm, 90mW class 3B laser
<b>Count modes</b>	Raw counts, #/m <sup>3</sup> , #/ft <sup>3</sup> , #/liter in Cumulative or Differential mode
<b>Counting efficiency</b>	50 % @ 0.3 µm; 100 % for particles > 0.45 µm (per ISO 21501)
<b>Zero count</b>	1 count/5 minute (JIS B9921)
<b>Concentration limits</b>	10 % at 4,000,000 particles per ft <sup>3</sup> (per ISO 21501)
<b>Data storage</b>	10,000 records (rotating buffer)
<b>Alarms</b>	User selected particle channels and limits
<b>Display</b>	QVGA color with backlight
<b>Delay time</b>	0 to 24 hours
<b>Sample inlet</b>	Isokinetic probe
<b>Security</b>	Administrator password controlled (optional)
<b>Communication mode</b>	USB or Ethernet
<b>Dimensions (L x W x D)</b>	27.2 cm x 9.9 cm x 5.3 cm (10.7 in x 3.9 in x 2.1 in)
<b>Weight</b>	0.68 kg (1.5 lb)
<b>Power adapter</b>	100 V ac to 240 V ac, 12 V dc, 2.5 A
<b>Rechargeable battery</b>	Li-ion 7.4 V 2600 mAh
<b>Battery duration/charge time</b>	10 hours typical use (5 hours continuous sampling)/3.5 hours
<b>Calibration</b>	PSL particles in air (NIST traceable)
<b>Operating environment</b>	50 °F to 104 °F (10 °C to 40 °C)/< 95 % non-condensing relative humidity
<b>Storage environment</b>	14 °F to 122 °F (-10 °C to 50 °C)/Up to 98 % non-condensing relative humidity
<b>Warranty</b>	One-year
<b>Accessories included</b>	Cradle for charging and convenient USB and Ethernet communications, Ethernet cable, USB cable, 12 V dc power supply, zero count inlet-filter, filter adapter, sample inlet protective cap, hard case, getting started manual and users manual CD

## Other IAQ tools from Fluke



**CO-205 Aspirator Kit** for flue gas sampling using Fluke family of gas measuring devices.

**CO-220 Carbon Monoxide Meter** measures CO levels in industrial environments, commercial or residential buildings where accumulation of combustion gas is possible.

**Fluke 922 Airflow Meter** makes airflow measurements easy by combining differential pressure, airflow, and velocity into a single, rugged meter.

**Fluke 971 Temperature Humidity Meter** takes accurate humidity and temperature readings in the air for maintaining optimal comfort levels and good indoor air quality for facility maintenance and utility technicians, and HVAC-service contractors.

**Fluke 975 AirMeter™** combines 5 powerful air quality tools into one for measuring essential IAQ parameters: temperature, humidity, dew point and wet bulb temperature, air volume, air velocity, CO, CO<sub>2</sub>, and % of outdoor air calculation.

## Ordering information

Fluke-985	Airborne Particle Counter
Fluke-CO-205	Aspirator Kit
Fluke-CO-220	Carbon Monoxide Meter
Fluke-922	Airflow Meter
Fluke-971	Temperature Humidity Meter
Fluke-975	AirMeter™

**Fluke.** *Keeping your world up and running.*®

**Fluke Corporation**  
PO Box 9090, Everett, WA 98206 U.S.A.

**Fluke Europe B.V.**  
PO Box 1186, 5602 BD  
Eindhoven, The Netherlands

**For more information call:**  
In the U.S.A. (800) 443-5853 or  
Fax (425) 446-5116  
In Europe/M-East/Africa +31 (0) 40 2675 200 or  
Fax +31 (0) 40 2675 222  
In Canada (800)-36-FLUKE or  
Fax (905) 890-6866  
From other countries +1 (425) 446-5500 or  
Fax +1 (425) 446-5116  
Web access: <http://www.fluke.com>

©2012 Fluke Corporation.  
Specifications subject to change without notice.  
Printed in U.S.A. 3/2012 4148253A D-EN-N

**Modification of this document is not permitted without written permission from Fluke Corporation.**